

testo 835 红外测温仪



4

50:1

(testo 835-H1)

testo 835

1500 °C

订购信息

testo 835-T1

智能红外测量技术领域

testo 835-T2

在高温应用中的优势

1500 °C

testo 835-T1

testo 835-T1

4



0560 8351

testo 835-T2

testo 835-T2

4



0560 8352

testo 835-H1

具有综合表面湿度测量功能的专用仪器

testo 835-H1

testo 835-H1

4












0560 8353

技术数据









	testo 835-T1	testo 835-T2	testo 835-H1
红外传感器			
	50: 1		
	4		
	8 ~ 14µm		
	-30 ~ +600 °C	-10 ~ +1500 °C	-30 ~ +600 °C
±1	±2.5 °C (-30.0 ~ -20,1 °C) ±1.5 °C (-20.0 ~ -0,1 °C) ±1.0 °C (+0.0 ~ +99.9 °C) ±1% ()	±2.0 °C ±1%	±2.5 °C (-30.0 ~ -20.1 °C) ±1.5 °C (-20.0 ~ -0.1 °C) ±1.0 °C (+0.0 ~ +99.9 °C) ±1% ()
	0.1 °C	0.1 °C (-10.0 ~ +999.9 °C) 1 °C (+1000.0 ~ +1500.0 °C)	0.1 °C
K型热电偶(NiCr-Ni)			
	-50 ~ +600 °C	-50 ~ +1000 °C	-50 ~ +600 °C
±1	±(0.5 °C +0.5%)		
	0.1 °C		
testo湿度传感器			
	-	-	0 ~ 100 % RH
±1	-	-	±2 %RH ±0.5 °C
	-	-	0.1 °C 0.1 %RH 0.1 °Ctd
仪器参数			
	0.10 ~ 1.00 (0.01)		
	20		
	/		
	200		
(/)			
	-20 ~ +50 °C		
	-30 ~ +50 °C		
/	ABS + PC		
	193 x 166 x 63 mm		
	514 g		
	3 AA (USB)		
	25 (25°C) 10 (25°C)		
	30 s 120 s		
	EN 61326-1: 2006		
	1	www.testo.com.cn	

探头一览

探头类型	图示	量程	精度	响应时间 t_{99}	订货号
空气探头					
1.2 K		-60 ~ +400 °C	2 ¹⁾	25 s	0602 1793
浸入/插入式探头					
K / 1.2		-60 ~ +1000 °C	1 ¹⁾	2 s	0602 0593
/ 1.2 K		-60 ~ +800 °C	1 ¹⁾	3 s	0602 2693
/ 1.2 K		-60 ~ +400 °C	2 ¹⁾	7 s	0602 1293
表面探头					
1.2 K +500°C,		-60 ~ +300 °C	2 ¹⁾	3 s	0602 0393
K 1.2		0 ~ +300 °C	2 ¹⁾	5 s	0602 0193
1.2 K		-60 ~ +400 °C	2 ¹⁾	30 s	0602 1993
1.2 K +500°C		-60 ~ +300 °C	2 ¹⁾	3 s	0602 0993
1.2 K		-60 ~ +1000 °C	1 ¹⁾	20 s	0602 0693

1) EN 60751, -40 ~ +1000/+1200 °C 1 / 2

探头一览

探头类型	图示	量程	精度	响应时间 t_{99}	订货号
表面探头					
680 mm K (1.6)		-50 ~ +250 °C	2 ¹⁾	3 s	0602 2394
20N K 1.6		-50 ~ +170 °C	2 ¹⁾		0602 4792
10N K 1.6		-50 ~ +400 °C	2 ¹⁾		0602 4892
K Ø 120 mm +120 °C 1.5		-50 ~ +120 °C	1 ¹⁾	90 s	0628 0020
5 ~ 65 mm +280 °C K 1.2		-60 ~ +130 °C	2 ¹⁾	5 s	0602 4592
K		-60 ~ +130 °C	2 ¹⁾	5 s	0602 0092
K 15 ~ 25 mm +130 °C 1.2		-50 ~ +100 °C	2 ¹⁾	5 s	0602 4692
食品探头					
IP65) K (1.2		-60 ~ +400 °C	2 ¹⁾	7 s	0602 2292

1) EN 60751 -40~+1000/+1200 °C 1/2

附件一览

附件		订货号
		0440 0950
USB		0449 0047
	(1 10m 25 mm) =0.93 +300°C	0554 0051
	(14g) +260°C	0554 0004
ISO	/ +60°C +120°C +180°C	0520 0002
ISO	/ -18°C 0°C +60°C	0520 0401
ISO	/ / 0°C +150°C +300°C	0520 0021

www.testo.com.cn

德图中国总部

()

全国服务热线:400 882 7833

www.testo.com.cn

487 23 401

200233
021-6482 9968
info@testo.com.cn

()

